


- 78-Spring
- 80-Tread
- 84-Thermo-insulated hatch
- 85-Ladder bracket
- 86-Hinge
- 88-Side bracket
- 90-handrail
- 93-stile end
- 94-Stringer (ladder side element)
- 686-Architraves LXL-PVC FAKRO

P	S	Z	G
Board movement after opening	Tread width	Tread thickness	Distance between treads
[cm]	[cm]	[cm]	[cm]
3	8	2	25

LTK Energy (4s) - Loft ladder dimensions										
H	H _{min}	A	B	K	R	C	E	T	WxL	MxN
Room height	Min. Room height	Width ceiling opening dimensions	Length ceiling opening dimensions	Folded ladder height	Swing space	Distance after ladder unfolding	Tread length	Box height	Box external dimensions	Internal box dimensions
[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]
280	235	60	120	35	164	129	34	18	58x118,4	54x114
		70	120						68x118,4	64x114
		70	130						68x128,4	64x124
		70	140						68x138,4	64x134
305	243	60	130	178	139	34	18	58x128,4	54x124	
		70	130					68x128,4	64x124	
		70	140					68x138,4	64x134	

FAKRO

LTK Energy (3s)



Warning! The present drawing is for informational-demonstrative purposes only and as such cannot constitute a basis for performance. All dimensions presented in this drawing should be verified on site. Because of the fact that the drawing is a schematic one, FAKRO shall not assume any responsibility for the actual installation quality. This drawing is FAKRO's property and cannot be published or used publicly without our written consent.

Technical drawing:
The LTK Energy (3s) Loft Ladder

FORMAT:
A4

SCALE:
1:20/1:10

DATE:
03.2021