


- 79-Fire-rated hatch
- 80-Tread
- 86-Hinge
- 88-Side bracket
- 90-LXH handrail
- 93-LXS stile end
- 94-Stringer (ladder side element)
- 686-Finishing lining slats LXL-PVC FAKRO
- 714-Fire-resistant sealant
- 715-Insulation:rock wool with a min.density of 60kg/m³
- 716-Spacing washer

P	S	E
Hatch board movement after opening	Tread width	Tread length
[cm]	[cm]	[cm]
5	8	34

LWF 60 - Loft ladder dimensions										
H	H	A	B	K	R	C	T	WxL	MxN	G
Room height	Min. Room height	Width ceiling opening dimensions	Length ceiling opening dimensions	Folded loft ladder height	Swing space	Distance after ladder unfolding	Box height	Outside box dimensions	Inside box dimensions	Distance between treads
[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]
280	234	60	120	38	164	129	22,5	58x118	54x114	25
		70	120					68x118	64x114	
		70	130					68x128	64x124	
		70	140					68x138	64x134	
		86	130					84x128	80x124	
305	242	70	130	178	139	22,5	68x128	64x124	25	
		70	140				68x138	64x134		
		86	130				84x128	80x124		



LWF 60 (3s)



Technical drawing:
The LWF 60 Loft Ladder

FORMAT:
A4

SCALE:
1:20/1:10

DATE:
03.2021

Warning! The present drawing is for informational-demonstrative purposes only and as such cannot constitute a basis for performance. All dimensions presented in this drawing should be verified on site. Because of the fact that the drawing is a schematic one, FAKRO shall not assume any responsibility for the actual installation quality. This drawing is FAKRO's property and cannot be published or used publicly without our written consent.