



- 1-Water draining gutter FAKRO
- 2-Polyurethane insulating wedge
- 3-Tile supporting profile
- 4-XDP FAKRO vapour permeable collar
- 5-Tress made of sheep wool FAKRO (XDP)
- 6-Blocks made of sheep wool FAKRO (XDP)
- 17-Rafter
- 38-Installation bracket
- 109-XDS air-tight flashing FAKRO
- 112-FSP P2 smoke ventilation window FAKRO
- 411-EHS flashing upper element FAKRO
- 412-EHS flashing lower element FAKRO
- 413-EHS flashing side element FAKRO

FSP P2			
Frame width S[mm]	Frame height H[mm]	Max. actual smoke ventilation area Aa [m ²]	Window symbol
777	1398	0,53	07
937	1398	0,65	09
1137	1178	0,67	10
	1398	0,8	11
1337	978	0,65	12

FAKRO		FORMAT: A3	SCALE: 1:10/1:5	DATE: 12.2022
FSP P2	EHS	TILE	20° - 60°	

Vertical and horizontal cross-section:
FSP P2 smoke ventilation window with EHS flashing for
profiled roofing materials

Warning! The present drawing is for informational-demonstrative purposes only and as such cannot constitute a basis for performance. All dimensions presented in this drawing should be verified on site. Because of the fact that the drawing is a schematic one, FAKRO shall not assume any responsibility for the actual installation quality on the roof. This drawing is FAKRO's property and cannot be published or used publicly without our written consent.